

GBIC Gigabit Interface Converter

GBIC-SX / Super SX

- ✎ Compliant with IEEE 802.3z Gigabit standard
- ✎ Industry Standard : Gigabit Interface Converter Standard
- ✎ Wavelength: 850nm
- ✎ Bit Rate : up to 1.25Gbps
- ✎ Dual Power Supply : 3.3 / 5 Voltage
- ✎ Connector: Duplex SC connector
- ✎ Hot Pluggable
- ✎ Class 1 laser product complies with En60825-1
- ✎ Transmission distance : 550m , 2Km (Super SX)



GBIC-LX

- ✎ Compliant with IEEE 802.3z Gigabit standard
- ✎ Industry Standard : Gigabit Interface Converter Standard
- ✎ Wavelength: 1310 nm
- ✎ Bit Rate : up to 1.25Gbps
- ✎ Dual Power Supply : 3.3 / 5 Voltage
- ✎ Connector: Duplex SC connector
- ✎ Hot Pluggable
- ✎ Class 1 laser product complies with En60825-1



Specification

SX Output - 3 (max.) ~ - 9.5dBm , Sensitivity - 20 (max.)dBm
LX Output - 4 (max.) ~ - 9.5dBm , Sensitivity - 18 (max.)dBm

Order Information

9400-100G	GBIC 1000 SX /SC / 0.5 km , 3.3/5V ,Multi-mode
9400-110G	GBIC 1000 Super SX/SC / 2km , 3.3/5V,Multi-mode
9400-200G	GBIC 1000 LX /SC/10km,3.3/5V,Single-mode
9400-300G	GBIC 1000 LHX/SC 30km,3.3/5V,Single-mode
9400-500G	GBIC 1000 XD/SC/50km, 3.3/5V , Single-mode
9400-800G	GBIC 1000 ZX/LC/80km, 3.3/5V , Single-mode

