

# SFP Small Form Factor Pluggable

## Mini GBIC-SX / Super SX

- ✎ Compliant with IEEE 802.3z Gigabit standard
- ✎ Industry Standard : Small Form Pluggable (SFP) package
- ✎ Wavelength: 850nm
- ✎ Bit Rate : up to 1.25Gbps
- ✎ Power Supply : 3.3 Voltage
- ✎ Connector: Duplex LC connector
- ✎ Hot Pluggable
- ✎ Class 1 laser product complies with En60825-1
- ✎ Transmission distance : 550m , 2Km (Super SX)



## Mini GBIC-LX

- ✎ Compliant with IEEE 802.3z Gigabit standard
- ✎ Industry Standard : Small Form Pluggable (SFP) package
- ✎ Wavelength: 1310 nm
- ✎ Bit Rate : up to 1.25Gbps
- ✎ Power Supply : 3.3 Voltage
- ✎ Connector: Duplex LC connector
- ✎ Hot Pluggable
- ✎ Class 1 laser product complies with En60825-1



## Specification

SX Output - 3 (max.) ~ - 9.5dBm , Sensitivity - 20 (max.)dBm  
LX Output - 4 (max.) ~ - 9.5dBm , Sensitivity - 18 (max.)dBm

## Order Information

9500-100M	Mini GBIC (SFP) 1000 SX /LC / 0.5 km , 3.3V ,Multi-mode
9500-110M	Mini GBIC (SFP) 1000 Super SX/LC / 2km , 3.3V,Multi-mode
9500-200M	Mini GBIC (SFP) 1000 LX /LC/10km,3.3V,Single-mode
9500-300M	Mini GBIC (SFP) 1000 LHX/LC 30km,3.3V,Single-mode
9500-500M	Mini GBIC (SFP) 1000 XD/LC/50km, 3.3V , Single-mode
9500-800M	Mini GBIC (SFP) 1000 ZX/LC/80km, 3.3V , Single-mode

